



Pressure Clips



The installation variant with the the pressure clips is particularly ideal when there is little installation height available under the ceiling, for example for use on intermediate ceilings and partition walls. With the small installation dimensions, fire alarm cables and small power cables for safety lighting systems, for example,

can be laid in a space-saving manner. The version of the pressure clip is suitable for fixing with gas pressure nailers. For installation, the hips of the pressure clips are simply bent downwards without tools and the cables pushed in from the side.


OBO Bettermann SIA

Tel.: +371 67802050

www.obo.lv

Pressure clips


Pressure clip for 8 cables



Type	No. of conductors NYM 3 x 1.5	Color	Pack Piece	Weight kg/100	Item no.
2032	8	Light grey	50	1,371	2205017

Standard version for general use, e.g. on intermediate ceilings and partition walls. Clamping height 9 mm – with spacer 13 mm. Fastening hole: 6 mm Ø.


Pressure clip for 8 cables, connectable



Type	No. of conductors NYM 3 x 1.5	Color	Pack Piece	Weight kg/100	Item no.
2032 AS	8	Light grey	50	1,3	2205052

Version suitable for fixing with gas pressure nail gun (i.e. by SPIT), for example for use on intermediate ceilings and partition walls. Clamping height: 9 mm, with spacer 13 mm. Fastening hole: 7 mm Ø.


Pressure clip for 10 cables



Type	No. of conductors NYM 3 x 1.5	Color	Pack Piece	Weight kg/100	Item no.
2034	10	Light grey	50	1,169	2205041

Standard version for general use, e.g. on intermediate ceilings and partition walls. Clamping height 9 mm – with spacer 13 mm. Fastening hole: 6 mm Ø.


Pressure clip for 10 cables, connectable



Type	No. of conductors NYM 3 x 1.5	Color	Pack Piece	Weight kg/100	Item no.
2034 AS	10	Light grey	50	1,13	2205054

With moulded push-fit plug, 6 mm Ø.
For max. 16 cables NYM 3 x 1.5 mm²


Pressure clip for 16 cables



Type	No. of conductors NYM 3 x 1.5	Color	Pack Piece	Weight kg/100	Item no.
2033	16	Light grey	25	2,077	2205033

Standard version for general use, e.g. on intermediate ceilings and partition walls. Clamping height 9 mm – with spacer 13 mm. Fastening hole: 6 mm Ø.


Pressure clip for 16 cables, connectable



Type	No. of conductors NYM 3 x 1.5	Color	Pack Piece	Weight kg/100	Item no.
2033 AS	16	Light grey	25	2,1	2205053

Version suitable for fixing with gas pressure nail gun (i.e. by SPIT), for example for use on intermediate ceilings and partition walls. Clamping height: 9 mm, with spacer 13 mm. Fastening hole: 7 mm Ø.


Pressure clip with push-fit anchor



Type	No. of conductors NYM 3 x 1.5	Color	Pack Piece	Weight kg/100	Item no.
2033 STD	16	Light grey	25	1,037	2204541

With moulded push-fit plug, 6 mm Ø.
For max. 16 cables NYM 3 x 1.5 mm²

Knock-in anchor



Type	Dowel Ø mm	Length mm	Pull-out force N mini/concrete	Pack Piece	Weight kg/100	Item no.
910 SD 6X40	6	40	260	100	0,555	2351064

Knock-in anchor: steel, electrogalvanised and transparently passivated.

OBO Bettermann SIA

Tel.: +371 67802050 • E-past: obo@obo.lv
www.obo.lv